


Uponor Aqua Ambient point drain inlet elb. super/arco FI 50

1136450

- Connection to waste pipes DN 50
- Flow rate: 0,4 l/s
- For low floor constructions
- Material grate: stainless-steel
- Material body: polypropylene



About Uponor Aqua Ambient point drain inlet elb. super/arco

Specification

- Available in different sizes: 600, 700, 800, 900, 1000mm
- Wide sealing collar (30mm) ensuring tight jointing to the floor construction
- Adjustable height and fixable legs for integration in every kind of floor construction
- Wide range compatible with all common waste outlet pipework.

Application


- Bathroom greywater applications

Certification

- Technical assessment acc BS EN 1253

Uponor Aqua Ambient point drain inlet elb. super/arco FI 50

1136450



Product code

Item no EAN	6414900483483
Item no GF	35001136450
Item no GTIN	06414900483483

Dimensions

Item Unit Height	80
Item Unit Length	220
Item Unit Weight	0,42
Item Unit Width	220
Item_UOM	pce

Measurements

Length (l1)	120
Outer Diameter_do	220
Outer Diameter_do1	50
Z Measurement h	55
Z Measurement h1	38
Z Measurement h2	14,5
Z	98

Packaging

Packaging GTIN PL1	06414900369114
Packaging GTIN PL4	06414900370042
Packaging Height PL1	90
Packaging Height PL4	1940
Packaging Length PL1	230
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	300
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,0046575
Packaging Volume PL4	1,8624
Packaging Weight PL1	0,53
Packaging Weight PL4	169
Packaging Width PL1	225
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com