

## Uponor Aqua Ambient point drain inlet c standard FI 50

**1136458**

- Connection to waste pipes DN 50 or DN 110
- Flow rate: DN 50 0,8 l/s, DN 110 1,4 l/s
- Material grate: stainless-steel
- Material body: Polypropylene

### About Uponor Aqua Ambient point drain inlet c standard

#### Specification

- Available in different sizes: 600, 700, 800, 900, 1000mm
- Wide sealing collar (30mm) ensuring tight jointing to the floor construction
- Adjustable height and fixable legs for integration in every kind of floor construction
- Wide range compatible with all common waste outlet pipework.

#### Application

- Bathroom greywater applications

#### Certification

- Technical assessment acc BS EN 1253

## Uponor Aqua Ambient point drain inlet c standard FI 50

1136458

**Product code**

Item no EAN	6414900483551
Item no GF	35001136458
Item no GTIN	06414900483551

**Dimensions**

Item Unit Height	148.5
Item Unit Length	210
Item Unit Weight	0,35
Item Unit Width	210
Item_UOM	pce

**Measurements**

Length (l1)	107
Outer Diameter_do	210
Outer Diameter_do1	50
Z Measurement h	123,5
Z Measurement h1	83,4
Z Measurement h2	40,1
Z	100

**Packaging**

Packaging GTIN PL1	06414900369459
Packaging GTIN PL4	06414900370097
Packaging Height PL1	155
Packaging Height PL4	1940
Packaging Length PL1	230
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	180
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00802125
Packaging Volume PL4	1,8624
Packaging Weight PL1	0,52
Packaging Weight PL4	118,6

Packaging Width PL1	225
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavillion  
WD18 8GA, Watford  
UK

T +44 (0)1923 381212

E  
customerservice.uk.bfs@georgfi  
scher.com