


Uponor Aqua Ambient point drain inlet down classic/spot FI 50

1136463

- Connection to waste pipes DN 50
- Flow rate: 0,8 l/s
- Material grate: stainless-steel
- Material body: polypropylene



About Uponor Aqua Ambient point drain inlet down classic/spot

Specification

- Available in different sizes: 600, 700, 800, 900, 1000mm
- Wide sealing collar (30mm) ensuring tight jointing to the floor construction
- Adjustable height and fixable legs for integration in every kind of floor construction
- Wide range compatible with all common waste outlet pipework.

Application


- Bathroom greywater applications

Certification

- Technical assessment acc BS EN 1253

Uponor Aqua Ambient point drain inlet down classic/spot FI 50

1136463



Product code

Item no EAN	6414900483629
Item no GF	35001136463
Item no GTIN	06414900483629

Dimensions

Item Unit Height	137,5
Item Unit Length	210
Item Unit Weight	0,35
Item Unit Width	210
Item_UOM	pce

Measurements

Length (l1)	120
Outer Diameter_do	210
Outer Diameter_do1	49
Z Measurement h	176,8
Z Measurement h1	38,4
Z Measurement h2	135,9
Z	48,7

Packaging

Packaging GTIN PL1	06414900369473
Packaging GTIN PL4	06414900370110
Packaging Height PL1	155
Packaging Height PL4	1940
Packaging Length PL1	230
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	180
Packaging Type PL1	Base_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00802125
Packaging Volume PL4	1,8624
Packaging Weight PL1	0,6
Packaging Weight PL4	119,8
Packaging Width PL1	225
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb