

Uponor Aqua Ambient point drain inlet pass super/spot FI 50

1136466

- Connection to waste pipes DN 50
- Flow rate: 0,4 l/s
- For low floor constructions
- Material grate: stainless steel
- Material body: polypropylene

About Uponor Aqua Ambient point drain inlet pass super/spot

Specification

- Available in different sizes: 600, 700, 800, 900, 1000mm
- Wide sealing collar (30mm) ensuring tight jointing to the floor construction
- Adjustable height and fixable legs for integration in every kind of floor construction
- Wide range compatible with all common waste outlet pipework.

Application

- Bathroom greywater applications

Certification

- Technical assessment acc BS EN 1253

Uponor Aqua Ambient point drain inlet pass super/spot FI 50

1136466

Measurements

Inner_diameter_di1	45,7
Length (l1)	120
Outer Diameter_do	220
Outer Diameter_do1	50
Z Measurement h	55
Z Measurement h1	38
Z Measurement h2	38

Product code

Item no EAN	6414900483650
Item no GF	35001136466
Item no GTIN	06414900483650

Dimensions

Item Unit Height	80
Item Unit Length	220
Item Unit Weight	0,4
Item Unit Width	220
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900369398
Packaging GTIN PL4	06414900370141
Packaging Height PL1	90
Packaging Height PL4	1940
Packaging Length PL1	230
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	300
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,004761
Packaging Volume PL4	1,8624
Packaging Weight PL1	0,56
Packaging Weight PL4	178

Packaging Width PL1	230
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com