

## Uponor Aqua Ambient point drain inlet pass super/spot FI 50

**1136466**

- Connection to waste pipes DN 50
- Flow rate: 0,4 l/s
- For low floor constructions
- Material grate: stainless steel
- Material body: polypropylene

### About Uponor Aqua Ambient point drain inlet pass super/spot

#### Specification

- Available in different sizes: 600, 700, 800, 900, 1000mm
- Wide sealing collar (30mm) ensuring tight jointing to the floor construction
- Adjustable height and fixable legs for integration in every kind of floor construction
- Wide range compatible with all common waste outlet pipework.

#### Application

- Bathroom greywater applications

#### Certification

- Technical assessment acc BS EN 1253

## Uponor Aqua Ambient point drain inlet pass super/spot FI 50

1136466

**Measurements**

Inner_diameter_di1	45,7
Length (l1)	120
Outer Diameter_do	220
Outer Diameter_do1	50
Z Measurement h	55
Z Measurement h1	38
Z Measurement h2	38

**Product code**

Item no EAN	6414900483650
Item no GF	35001136466
Item no GTIN	06414900483650

**Dimensions**

Item Unit Height	80
Item Unit Length	220
Item Unit Weight	0,4
Item Unit Width	220
Item_UOM	pce

**Packaging**

Packaging GTIN PL1	06414900369398
Packaging GTIN PL4	06414900370141
Packaging Height PL1	90
Packaging Height PL4	1940
Packaging Length PL1	230
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	300
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,004761
Packaging Volume PL4	1,8624
Packaging Weight PL1	0,56
Packaging Weight PL4	178

Packaging Width PL1	230
Packaging Width PL4	800

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)