

Uponor Aqua Ambient point drain inlet down c standard FI 50

1136471

- Connection to waste pipes DN 50 or DN 110
- Flow rate: DN 50 0,8 l/s, DN 110 1,4 l/s
- Material grate: stainless-steel
- Material body: polypropylene

About Uponor Aqua Ambient point drain inlet down c standard

Specification

- Available in different sizes: 600, 700, 800, 900, 1000mm
- Wide sealing collar (30mm) ensuring tight jointing to the floor construction
- Adjustable height and fixable legs for integration in every kind of floor construction
- Wide range compatible with all common waste outlet pipework.

Application

- Bathroom greywater applications

Certification

- Technical assessment acc BS EN 1253

Uponor Aqua Ambient point drain inlet down c standard FI 50

1136471

Product code

Item no EAN	6414900483704
Item no GF	35001136471
Item no GTIN	06414900483704

Dimensions

Item Unit Height	176
Item Unit Length	210
Item Unit Weight	0,34
Item Unit Width	210
Item_UOM	pce

Measurements

Length (l1)	107
Outer Diameter_do	210
Outer Diameter_do1	50
Z Measurement h	176
Z Measurement h1	40,1
Z Measurement h2	86,9
Z	49

Packaging

Packaging GTIN PL1	06414900369428
Packaging GTIN PL4	06414900370172
Packaging Height PL1	150
Packaging Height PL4	1940
Packaging Length PL1	230
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	180
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,0077625
Packaging Volume PL4	1,8624
Packaging Weight PL1	0,52
Packaging Weight PL4	103,6

Packaging Width PL1	225
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com