


Uponor Vario S manifold FM 8xG3/4 Euro - G1

1140839

- Supply beam with flowmeters for balancing and shutoff, with memory ring
- Return beam with valves for shutoff, with hand caps



About Uponor Vario S manifold FM

Specification


- Made of stainless steel
- With integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill&drain points in supply and return,
- Loop connection G3/4" eurocone
- Loop pitch 50 mm
- Header pitch 215 mm

Application

- For underfloor-heating and -cooling
- Applicable with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

Uponor Vario S manifold FM 8xG3/4 Euro - G1

1140839



Technical data

Item no EAN	6414900440462
Item no GTIN	06414900440462
Item no NRF	8361366
Item no LVI	2022296
Item (unit of measurement)	pce
Length (l)	514 mm
Length (l1)	77 mm
Length (l2)	87 mm
Z-measurement b	50 mm
Z-measurement b1	217 mm
Z-measurement h	73 mm
Z-measurement h1	30 mm
Z-measurement h2	50 mm
Z-measurement k	435 mm
Z-measurement k1	336 mm
Z-measurement w	357 mm
Packaging Quantity 1	1
Packaging Quantity 4	54
Packaging GTIN PL1	06414900500784
Packaging GTIN PL4	06414900322942
Item Unit Height	40 mm
Item Unit Weight	5 kg
Item Unit Width	235 mm

Technical documents

Download documents here

www.uponor.com/en-gb