



Uponor Vario S manifold FM 16xG3/4 Euro - G1

1140847

- Supply beam with flowmeters for balancing and shutoff, with memory ring
- Return beam with valves for shutoff, with hand caps
- With primary connection G1



About Uponor Vario S manifold FM

Specification



- Made of stainless steel, with integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill & drain points in supply/return
- Loop connection G3/4" Eurocone c-c 50 mm
- Header pitch 215 mm

Application

- For underfloor-heating and -cooling
- For use with with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

Uponor Vario S manifold FM 16xG3/4 Euro - G1

1140847



Status

Item Available From date

2024-05-01

Product code

Item no EAN

6414900440547

Item no GF

35001140847

Item no GTIN

06414900440547

Dimensions

Item Unit Height

40

Item Unit Length

910

Item Unit Weight

9

Item Unit Width

235

Item_UOM

pce

Measurements

LENGTH_L

914

Length (l1)

77

Length (l2)

87

Z Measurement b

50

Z Measurement b1

217

Z Measurement h

73

Z Measurement h1

30

Z Measurement h2

50

Z Measurement k

835

Z Measurement k1

336

Z Measurement w

357

Packaging

Packaging GTIN PL1

06414900500869

Packaging GTIN PL4

06414900501354

Packaging Height PL1

47

Packaging Height PL4	996
Packaging Length PL1	967
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	36
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,014452782
Packaging Volume PL4	0,95616
Packaging Weight PL1	9,2
Packaging Weight PL4	356
Packaging Width PL1	318
Packaging Width PL4	800

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb