



Uponor Vario S manifold LS 14xG3/4 Euro - G1

1140875

- Supply beam with lock shield valves for balancing and shutoff
- Return beam with valves for shutoff, with hand caps
- With primary connection G1



About Uponor Vario S manifold LS

Specification



- Made of stainless steel, with integrated valves
- Connection right or left with flat sealing
- Integrated airvents and fill & drain points in supply/return
- Loop connection G3/4" Eurocone c-c 50 mm
- Header pitch 215 mm

Application

- For underfloor-heating and -cooling
- For use with with actuators 1141676 (230V) and 1141677 (24V)
- Max. pressure: 6 bar at 60°C

Uponor Vario S manifold LS 14xG3/4 Euro - G1

1140875



Status

Item Available From date

2024-05-01

Product code

Item no EAN

6414900440820

Item no GTIN

06414900440820

Item no VVS

046230114

Dimensions

Item Unit Height

40

Item Unit Length

810

Item Unit Weight

7,9

Item Unit Width

235

Item_UOM

pce

Measurements

Length (l1)

814

Length (l2)

87

Z Measurement b

50

Z Measurement b1

217

Z Measurement h

73

Z Measurement h1

30

Z Measurement h2

50

Z Measurement k

735

Z Measurement k1

336

Z Measurement w

357

Packaging

Packaging GTIN PL1

06414900500999

Packaging GTIN PL4

06414900501484

Packaging Height PL1

47

Packaging Height PL4

996

Packaging Length PL1	967
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL4	36
Packaging Type PL1	Base_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,014452782
Packaging Volume PL4	0,95616
Packaging Weight PL1	8,2
Packaging Weight PL4	320
Packaging Width PL1	318
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb