


Uponor S-Press PLUS Adapter M+V 32-28CU-SST

1145406

- Adapter fit to Copper and Stainless-steel pipes using pressing jaw type M or V (metal press connection)
- Must use Uponor Multilayer press jaws on the Multilayer connection
- Made of DZR brass (lead free)
- With fixed press sleeve, stop ring, pressed identification, colour code and test safety
- Press without bevel (Multilayer connection)



About Uponor S-Press PLUS Adapter M+V

Specification

- Unique press indicator foil
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour coded
- Fixed press sleeve with inspection windows
- Precise jaw location
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

Tested/approved according to BS EN ISO 21003 Multilayer piping systems for hot and cold water installations inside buildings for application class 1,2,4,5/10bar

Domestic water services: The permanent operating temperature from 20°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.

Domestic cold water services : where the water temperature does not exceed 20°C at a maximum permanent operating pressure of 16bar.

Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

Certification


UK Reg4 approval

- WRAS or
- KIWA

to meet the requirements of the Water Supply (Water Fittings) Regulations 1999

Uponor S-Press PLUS Adapter M+V 32-28CU-SST

1145406



Status

Item Available From date

2025-03-01

Product code

Item no EAN	6414900390064
Item no GF	35001145406
Item no GTIN	06414900390064
Item no LVI	1720864
Item no RSK	1885652

Dimensions

Item Unit Height	37
Item Unit Length	63
Item Unit Weight	0,129
Item Unit Width	37
Item_UOM	pce

Measurements

LENGTH_L	63
Length (l1)	27
Length (l2)	28
z1	8

Packaging

Packaging GTIN PL1	06414900390392
Packaging GTIN PL3	06414900448475
Packaging GTIN PL4	06414900445993
Packaging Height PL1	89
Packaging Height PL3	188
Packaging Height PL4	714
Packaging Length PL1	176
Packaging Length PL3	277

Packaging Length PL4	1200
Packaging Quantity PL1	5
Packaging Quantity PL3	40
Packaging Quantity PL4	1920
Packaging Type PL1	Base_Box
Packaging Type PL3	Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001049488
Packaging Volume PL3	0,009321604
Packaging Volume PL4	0,68544
Packaging Weight PL1	0,680
Packaging Weight PL3	5,566
Packaging Weight PL4	290
Packaging Width PL1	67
Packaging Width PL3	179
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
 WD18 8GA, Watford
 UK

T +44 (0)1923 927000
 E enquiries.uk@uponor.com

www.uponor.com/en-gb