


GF JRGUMAT thermostatic mixing valve 3400 40°C DN50

1149459

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 40°C (30-45°C)
- Material: gunmetal
- Connection: male thread



About GF JRGUMAT thermostatic mixing valve 3400 40°C

Specification

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- For use within potable water systems
- Safe and constant mixed water temperature
- Excess-temperature protection in systems using alternative forms of energy such as solar thermal and bio-mass energy systems
- Central and decentralized hot water mixing for single family and multi-family homes, hospitality buildings and sports facilities

GF JRGUMAT thermostatic mixing valve 3400 40°C DN50

1149459



Product code

Item no EAN	7613263101440
Item no GF	350760012
Item no GTIN	07613263101440
Item no RSK	4927925
Item no VVS	723481012

Dimensions

Item Unit Height	154.5
Item Unit Length	180
Item Unit Weight	3,51
Item Unit Width	94.5
Item_UOM	pce

Measurements

Length (l1)	70
Length (l2)	110
Z Measurement h1	60
Z Measurement h2	85
Z Measurement h3	70

Packaging

Packaging GTIN PL1	06414900057646
Packaging Height PL1	126
Packaging Length PL1	290
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,00807534
Packaging Weight PL1	3,82
Packaging Width PL1	221

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb