


GF JRGUMAT thermostatic mixing valve 3400 55°C DN40

1149473

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Material: gunmetal
- Connection: male thread



About GF JRGUMAT thermostatic mixing valve 3400 55°C

Specification

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- For use within potable water systems
- Safe and constant mixed water temperature
- Excess-temperature protection in systems using alternative forms of energy such as solar thermal and bio-mass energy systems
- Central and decentralized hot water mixing for single family and multi-family homes, hospitality buildings and sports facilities

GF JRGUMAT thermostatic mixing valve 3400 55°C DN40

1149473



Status

Item Available From date

2025-08-25

Product code

Item no EAN

7613263101723

Item no GF

350760113

Item no GTIN

07613263101723

Item no RSK

4927923

Dimensions

Item Unit Height

135

Item Unit Length

150

Item Unit Weight

2,1

Item Unit Width

75

Item_UOM

pce

Measurements

Length (l1)

58

Length (l2)

92

Z Measurement h1

50

Z Measurement h2

77

Z Measurement h3

58

Packaging

Packaging GTIN PL1

06414900057752

Packaging Height PL1

105

Packaging Length PL1

250

Packaging Quantity PL1

1

Packaging Type PL1

Base_Box

Packaging Volume PL1

0,005145

Packaging Weight PL1

2,34

Packaging Width PL1

196

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb