


GF JRGUMAT thermostatic mixing valve 3410 55°C DN65

1149522

- Temperature: max. 90°C
- Nominal pressure: PN10
- Factory setting: 55°C (45-65°C)
- Material: gunmetal
- Connection: flange



About GF JRGUMAT thermostatic mixing valve 3410 55°C

Specification

- Dimension range DN15 – DN80
- Different temperature ranges (20-80°C) and factory settings (e.g. 25, 40, 55 and 70°C)

Application

- For use within potable water systems
- Safe and constant mixed water temperature
- Excess-temperature protection in systems using alternative forms of energy such as solar thermal and bio-mass energy systems
- Central and decentralized hot water mixing for single family and multi-family homes, hospitality buildings and sports facilities

GF JRGUMAT thermostatic mixing valve 3410 55°C DN65

1149522



Measurements

Inner_diameter_di	65
Length (l1)	145
Length (l2)	290
Length (l3)	112
Z Measurement h1	82
Z Measurement h2	121

Product code

Item no EAN	7613263101778
Item no GF	350767216
Item no GTIN	07613263101778
Item no RSK	4927899

Dimensions

Item Unit Height	266.5
Item Unit Length	290
Item Unit Weight	22,5
Item Unit Width	185
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900169653
Packaging Height PL1	220
Packaging Length PL1	395
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0291115
Packaging Weight PL1	22,8499709871702
Packaging Width PL1	335

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb