Product data sheet




GF Hycleen AS balancing valve LegioTherm 2T DN15

1149709

- Temperature: max. 90°C
- Nominal pressure: PN10
- Material: gunmetal lead-free, stainless steel, EPDM
- Factory setting: 57°C (adjustable 0 - 90°C) thermal disinfection 70°C (adjustable 60 - 90°C)
- Connection: screw connection





About GF Hycleen AS balancing valve LegioTherm 2T

Specification

- Balancing valves: DN 15, 20, 25
- Flush valves: DN 15 & 20
- Central control interface with touch-screen
- Operating pressure: to 10 bar
- Operating temperature: +5°C to +90°C
- Materials: Gunmetal, Stainless steel, Plastics


Application

- Balancing of potable water hot circulation systems
- Ensure water exchange in potable water hot & cold pipe sections
- For buildings with complex water installations
- Ideal for retro-fit where existing installations experience poor hot water supply to outlets

GF Hycleen AS balancing valve LegioTherm 2T DN15

1149709





Status

Item Available From date	2026-03-01

Product code

Item no EAN	7613263102546
Item no GF	351110550
Item no GTIN	07613263102546
Item no LVI	2075242
Item no RSK	4883142

Dimensions

Item Unit Height	158
Item Unit Length	296
Item Unit Weight	0,82
Item Unit Width	175
Item_UOM	pce

Measurements

Length (l1)	75
Length (l2)	6
Length (l3)	24
Z Measurement b	90
Z Measurement d1	G3/4"
Z Measurement d2	G1/2"
Z Measurement d3	Rp1/4"
Z Measurement d3	Rp1/4"
Z Measurement h1	162
Z Measurement h2	50

Packaging

Packaging GTIN PL1	06414900170819
Packaging Height PL1	158
Packaging Length PL1	296
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0081844
Packaging Weight PL1	0,988
Packaging Width PL1	175

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+