

GF Hycleen AS power supply & communication cable 1,5m

1149711

- Description: For serial connection of Hycleen Automation System components (master, controller)
- incl. 2x M12 plugs, ROHS



About GF Hycleen AS power supply & communication cable

Specification

- Balancing valves: DN 15, 20, 25
- Flush valves: DN 15 & 20
- Central control interface with touch-screen
- Operating pressure: to 10 bar
- Operating temperature: +5°C to +90°C
- Materials: Gunmetal, Stainless steel, Plastics

Application

- Balancing of potable water hot circulation systems
- Ensure water exchange in potable water hot & cold pipe sections
- For buildings with complex water installations
- Ideal for retro-fit where existing installations experience poor hot water supply to outlets

GF Hycleen AS power supply & communication cable 1,5m

1149711



Measurements

Inner_diameter_di 6,8

Status

Item Available From date 2026-03-01

Product code

Item no EAN 7613263105127

Item no GF 351110581

Item no GTIN 07613263105127

Item no LVI 2075243

Item no RSK 4893321

Dimensions

Item Unit Height 15

Item Unit Length 260

Item Unit Weight 0,11

Item Unit Width 260

Item_UOM pce

Packaging

Packaging GTIN PL1 06414900170833

Packaging Height PL1 15

Packaging Length PL1 260

Packaging Quantity PL1 1

Packaging Type PL1 Plastic_Bag

Packaging Volume PL1 0,001014

Packaging Weight PL1 0,115

Packaging Width PL1 260

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb