Product data sheet



GF Hycleen AS power supply & communication cable 1,5m

1149711

- Description: For serial connection of Hycleen Automation System components (master, controller)
- incl. 2x M12 plugs, ROHS



About GF Hycleen AS power supply & communication cable

Specification

- Balancing valves: DN 15, 20, 25
- Flush valves: DN 15 & 20
- Central control interface with touch-screen
- Operating pressure: to 10 bar
- Operating temperature: +5°C to +90°C
- Materials: Gunmetal, Stainless steel, Plastics

Application

- Balancing of potable water hot circulation systems
- Ensure water exchange in potable water hot & cold pipe sections
- For buildings with complex water installations
- Ideal for retro-fit where existing installations experience poor hot water supply to outlets

GF Hycleen AS power supply & communication cable 1,5m

1149711



Status

Item Available From date	2026-03-01

Product code

Item no EAN	7613263105127
Item no GF	351110581
Item no GTIN	07613263105127
Item no LVI	2075243
Item no RSK	4893321

Dimensions

Item Unit Height	15
Item Unit Length	260
Item Unit Weight	0,11
Item Unit Width	260
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900170833
Packaging Height PL1	15
Packaging Length PL1	260
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,001014
Packaging Weight PL1	0,115
Packaging Width PL1	260

Measurements

Z Measurement d	14,5
Z Measurement d1	6,8

Technical documents

Download documents here

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E customerservice.uk.bfs@georgfischer.com

www.uponor.com/en-gb

+GF+