


GF Hycleen AS balancing valve LegioTherm 2T DN20

1149718

- Temperature: max. 90°C
- Nominal pressure: PN10
- Material: gunmetal lead-free, stainless steel, EPDM
- Factory setting: 57°C (adjustable 0 - 90°C) thermal disinfection 70°C (adjustable 60 - 90°C)
- Connection: screw connection



About GF Hycleen AS balancing valve LegioTherm 2T

Specification

- Balancing valves: DN 15, 20, 25
- Flush valves: DN 15 & 20
- Central control interface with touch-screen
- Operating pressure: to 10 bar
- Operating temperature: +5°C to +90°C
- Materials: Gunmetal, Stainless steel, Plastics

Application

- Balancing of potable water hot circulation systems
- Ensure water exchange in potable water hot & cold pipe sections
- For buildings with complex water installations
- Ideal for retro-fit where existing installations experience poor hot water supply to outlets

GF Hycleen AS balancing valve LegioTherm 2T DN20

1149718



Status

Item Available From date 2026-03-01

Product code

Item no EAN	7613263104212
Item no GF	351110590
Item no GTIN	07613263104212
Item no LVI	2075248
Item no RSK	4883143

Dimensions

Item Unit Height	180
Item Unit Length	300
Item Unit Weight	1,05
Item Unit Width	200
Item_UOM	pce

Measurements

Length (l1)	87
Length (l2)	7
Length (l3)	24
Z Measurement h1	169
Z Measurement h2	54

Packaging

Packaging GTIN PL1	06414900170901
Packaging Height PL1	180
Packaging Length PL1	300
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0108
Packaging Weight PL1	1,22

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb