


GF Hycleen AS 4-20mA cable Uni Controller 5m

1149735

- Cable to connect Uni Controller 4-20 mA connectors with actuators.
- Control and programming of actuators via the master.
- Connection: M12 Plug



About GF Hycleen AS 4-20mA cable Uni Controller

Specification

- Balancing valves: DN 15, 20, 25
- Flush valves: DN 15 & 20
- Central control interface with touch-screen
- Operating pressure: to 10 bar
- Operating temperature: +5°C to +90°C
- Materials: Gunmetal, Stainless steel, Plastics

Application

- Balancing of potable water hot circulation systems
- Ensure water exchange in potable water hot & cold pipe sections
- For buildings with complex water installations
- Ideal for retro-fit where existing installations experience poor hot water supply to outlets

GF Hycleen AS 4-20mA cable Uni Controller 5m

1149735



Status

Item Available From date 2026-03-01

Product code

Item no EAN 7613263109958

Item no GF 351110674

Item no GTIN 07613263109958

Item no RSK 4893518

Dimensions

Item Unit Height 15

Item Unit Length 5000

Item Unit Weight 0,2

Item Unit Width 15

Item_UOM pce

Packaging

Packaging GTIN PL1 06414900171113

Packaging Height PL1 30

Packaging Length PL1 250

Packaging Quantity PL1 1

Packaging Type PL1 Plastic_Bag

Packaging Volume PL1 0,001875

Packaging Weight PL1 0,21

Packaging Width PL1 250

Technical documents

Download documents here

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb