


GF Hycleen AS Master UK

1149736

- Description: Master for max. 50 Hycleen AS Controller
- Consisting of: touchscreen 10.1", power supply
- 2 plugs M12 for 2x 300m cable (500m with powerbox)
- 2 Rj45 jacks (Ethernet), 2 USB connections (read/write)
- USB jack (read only), relay output
- Screw set



About GF Hycleen AS Master

Specification


- Balancing valves: DN 15, 20, 25
- Flush valves: DN 15 & 20
- Central control interface with touch-screen
- Operating pressure: to 10 bar
- Operating temperature: +5°C to +90°C
- Materials: Gunmetal, Stainless steel, Plastics

Application

- Balancing of potable water hot circulation systems
- Ensure water exchange in potable water hot & cold pipe sections
- For buildings with complex water installations
- Ideal for retro-fit where existing installations experience poor hot water supply to outlets

GF Hycleen AS Master UK

1149736



Status

Item Available From date 2026-03-01

Product code

Item no EAN	7613263111487
Item no GF	351110679
Item no GTIN	07613263111487

Dimensions

Item Unit Height	300
Item Unit Length	400
Item Unit Weight	2,3
Item Unit Width	400
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900171120
Packaging Height PL1	300
Packaging Length PL1	410
Packaging Quantity PL1	1
Packaging Type PL1	Base_Box
Packaging Volume PL1	0,0492
Packaging Weight PL1	2,77789842064723
Packaging Width PL1	400

Measurements

Z Measurement h	214
-----------------	-----

Technical documents

Download documents here

Enquiries.uk@uponor.com

www.uponor.com/en-gb