

## GF Hycleen flow sensor DN20

**1149751**

- Temperature: max. 90°C
- Nominal pressure: PN16
- Material: brass
- Connection: screw connection, cable plug M8



### About GF Hycleen flow sensor

#### Specification

- 30 V DC power supplies for Hycleen Balance and Flush systems
- Communication and extension cables with M8 push-pull connectors
- BMS connection via Modbus RTU
- Temperature sensors PT1000 and 4–20 mA sensor adapters
- Flow sensors and drain surveillance sensors
- Insulation shells made of EPP for DN15 and DN20 valves
- Sensor extension cables and spare sensor components

#### Application

- Power supply and electrical connection of Hycleen Balance and Flush systems
- Communication and bus extension between Hycleen components
- Integration with building management systems (BMS)
- Temperature, flow, and leakage monitoring in drinking water installations
- Protection, insulation and installation support of hygiene flushing valves

## GF Hycleen flow sensor DN20

1149751



### Status

Item Available From date 2026-03-01

### Product code

Item no EAN	7613263106933
Item no GF	351110772
Item no GTIN	07613263106933
Item no LVI	2022357
Item no RSK	4893375

### Dimensions

Item Unit Height	85
Item Unit Length	190
Item Unit Weight	0,25
Item Unit Width	85
Item_UOM	pce

### Measurements

Length (l1)	15
Z Measurement h	999
Z Measurement h1	49
Z Measurement h2	32

### Packaging

Packaging GTIN PL1	06414900171175
Packaging Height PL1	100
Packaging Length PL1	200
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,002
Packaging Weight PL1	3
Packaging Width PL1	100

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavilion  
WD18 8GA, Watford  
UK

T +44 (0)1923 927000  
E [enquiries.uk@uponor.com](mailto:enquiries.uk@uponor.com)

[www.uponor.com/en-gb](http://www.uponor.com/en-gb)