

GF HT-PP pipe with single socket 32x3000mm

1150077

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket 32x3000mm

1150077



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652042350
Item no GF	4801003200721
Item no GTIN	08698652042350
Item no VVS	186020300

Dimensions

Item Unit Height	32
Item Unit Length	3000
Item Unit Weight	0,595
Item Unit Width	32
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900551830
Packaging GTIN PL2	06414900172929
Packaging Height PL1	32
Packaging Height PL2	175
Packaging Length PL1	3000
Packaging Length PL2	3000
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,003072
Packaging Volume PL2	0,03675
Packaging Weight PL1	0,595
Packaging Weight PL2	5,95

Packaging Width PL1	32
Packaging Width PL2	70
Measurements	
Wall thickness_s	20
Z Measurement d	39
Z Measurement d1	32
Z Measurement e	1,8
Z Measurement L1	45

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com