

GF HT-PP pipe with single socket 40x2000mm

1150079

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket 40x2000mm

1150079



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652042640
Item no GF	4801004001521
Item no GTIN	08698652042640
Item no VVS	186021200

Dimensions

Item Unit Height	40
Item Unit Length	2000
Item Unit Weight	0,508
Item Unit Width	40
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900551878
Packaging GTIN PL2	06414900172943
Packaging Height PL1	40
Packaging Height PL2	225
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,0032
Packaging Volume PL2	0,0405
Packaging Weight PL1	0,508
Packaging Weight PL2	5,08

Packaging Width PL1 40

Packaging Width PL2 90

Measurements

Wall thickness_s 20

Z Measurement d 50,3

Z Measurement d1 40

Z Measurement e 1,8

Z Measurement L1 45

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com