

GF HT-PP pipe with single socket 50x3000mm

1150087

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket 50x3000mm

1150087



Status

Item Available From date

2026-03-01

Product code

Item no EAN 8698652031385

Item no GF 4801005002621

Item no GTIN 08698652031385

Item no VVS 186022300

Dimensions

Item Unit Height 50

Item Unit Length 3000

Item Unit Weight 0,958

Item Unit Width 50

Item_UOM pce

Packaging

Packaging GTIN PL1 06414900551953

Packaging GTIN PL2 06414900173025

Packaging Height PL1 50

Packaging Height PL2 275

Packaging Length PL1 3000

Packaging Length PL2 3000

Packaging Quantity PL1 1

Packaging Quantity PL2 10

Packaging Type PL1 Piece

Packaging Type PL2 Bag

Packaging Volume PL1 0,0075

Packaging Volume PL2 0,099

Packaging Weight PL1 0,958

Packaging Weight PL2 9,58

Packaging Width PL1	50
Packaging Width PL2	120
Measurements	
Wall thickness_s	20
Z Measurement d	60
Z Measurement d1	50
Z Measurement e	1,8
Z Measurement L1	50

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com