


GF HT-PP pipe with single socket S20 75x3000mm

1150096

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification


- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket S20 75x3000mm

1150096



Status

Item Available From date

2026-03-01

Product code

Item no EAN	8698652031453
Item no GF	4801007503621
Item no GTIN	08698652031453
Item no VVS	186024300

Dimensions

Item Unit Height	75
Item Unit Length	3000
Item Unit Weight	1,531
Item Unit Width	75
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900552004
Packaging GTIN PL2	06414900173100
Packaging Height PL1	75
Packaging Height PL2	400
Packaging Length PL1	3000
Packaging Length PL2	3000
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,016875
Packaging Volume PL2	0,204
Packaging Weight PL1	1,531
Packaging Weight PL2	15,31

Packaging Width PL1	75
Packaging Width PL2	170
Measurements	
Wall thickness_s	20
Z Measurement d	85,2
Z Measurement d1	75
Z Measurement e	1,9
Z Measurement L1	55

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com