

GF HT-PP pipe with single socket S20 110x2000mm

1150102

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket S20 110x2000mm

1150102



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652031514
Item no GF	4801011004521
Item no GTIN	08698652031514
Item no VVS	186027200

Dimensions

Item Unit Height	110
Item Unit Length	2000
Item Unit Weight	2,157
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900600194
Packaging GTIN PL2	06414900173162
Packaging Height PL1	110
Packaging Height PL2	250
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,0242
Packaging Volume PL2	0,125
Packaging Weight PL1	2,157
Packaging Weight PL2	8,628

Packaging Width PL1	110
Packaging Width PL2	250
Measurements	
Wall thickness_s	20
Z Measurement d	120,6
Z Measurement d1	110
Z Measurement e	2,7
Z Measurement L1	65

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com