


GF HT-PP Pipe with single socket S16 110x2000mm

1150106

- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP Pipe with single socket S16

Specification


- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP Pipe with single socket S16 110x2000mm

1150106



Status

Item Available From date

2026-03-01

Product code

Item no EAN	8698652092683
Item no GF	4801011025421
Item no GTIN	08698652092683

Dimensions

Item Unit Height	110
Item Unit Length	2000
Item Unit Weight	2,398
Item Unit Width	110
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900600156
Packaging GTIN PL2	06414900173193
Packaging Height PL1	110
Packaging Height PL2	250
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,0242
Packaging Volume PL2	0,125
Packaging Weight PL1	2,398
Packaging Weight PL2	9,592
Packaging Width PL1	110

Packaging Width PL2 250

Measurements

Wall thickness_s 16

Z Measurement d 129,3

Z Measurement d1 110

Z Measurement e 3,4

Z Measurement L1 65

Technical documents

[Download documents here](#) 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com