

GF HT-PP pipe with single socket S20 125x2000mm

1150111

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket S20 125x2000mm

1150111



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652031583
Item no GF	4801012505421
Item no GTIN	08698652031583
Item no VVS	186028200

Dimensions

Item Unit Height	125
Item Unit Length	2000
Item Unit Weight	2,822
Item Unit Width	125
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900600255
Packaging GTIN PL2	06414900173247
Packaging Height PL1	125
Packaging Height PL2	275
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,03125
Packaging Volume PL2	0,15125
Packaging Weight PL1	2,822
Packaging Weight PL2	11,288

Packaging Width PL1	125
Packaging Width PL2	275

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb