

GF HT-PP pipe with single socket S20 160x2000mm

1150116

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket S20 160x2000mm

1150116



Status

Item Available From date 2026-03-01

Product code

| | |
|--------------|----------------|
| Item no EAN | 8698652031651 |
| Item no GF | 4801016006421 |
| Item no GTIN | 08698652031651 |
| Item no VVS | 186029200 |

Dimensions

| | |
|------------------|-------|
| Item Unit Height | 160 |
| Item Unit Length | 2000 |
| Item Unit Weight | 4,501 |
| Item Unit Width | 160 |
| Item_UOM | pce |

Packaging

| | |
|------------------------|----------------|
| Packaging GTIN PL1 | 06414900230810 |
| Packaging Height PL1 | 165 |
| Packaging Length PL1 | 2005 |
| Packaging Quantity PL1 | 1 |
| Packaging Type PL1 | Piece |
| Packaging Volume PL1 | 0,054586125 |
| Packaging Weight PL1 | 4,601 |
| Packaging Width PL1 | 165 |

Measurements

| | |
|------------------|-------|
| Wall thickness_s | 20 |
| Z Measurement d | 176,5 |
| Z Measurement d1 | 160 |
| Z Measurement e | 3,9 |
| Z Measurement L1 | 75 |

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com