

GF HT-PP pipe with single socket S20 160x3000mm

1150117

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket S20 160x3000mm

1150117



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652031668
Item no GF	4801016006521
Item no GTIN	08698652031668
Item no VVS	186029300

Dimensions

Item Unit Height	160
Item Unit Length	3000
Item Unit Weight	6,617
Item Unit Width	160
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900230827
Packaging Height PL1	165
Packaging Length PL1	3005
Packaging Quantity PL1	1
Packaging Type PL1	Piece
Packaging Volume PL1	0,081811125
Packaging Weight PL1	6,717
Packaging Width PL1	165

Measurements

Wall thickness_s	20
Z Measurement d	176,5
Z Measurement d1	160
Z Measurement e	3,9
Z Measurement L1	75

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com