


GF HT-PP double branch 87,5deg 110-110mm

1150169

- Grey, PP-material
- According to BS EN 1451



About GF HT-PP double branch 87,5deg

Specification


- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP double branch 87,5deg 110-110mm

1150169



Status

Item Available From date

2026-03-01

Product code

Item no EAN	8698652032092
Item no GF	4901211014121
Item no GTIN	08698652032092
Item no VVS	186411110

Dimensions

Item Unit Height	241
Item Unit Length	130
Item Unit Weight	0,811
Item Unit Width	268
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900554428
Packaging GTIN PL2	06414900231336
Packaging GTIN PL4	06414900104807
Packaging Height PL1	241
Packaging Height PL2	400
Packaging Height PL4	1200
Packaging Length PL1	130
Packaging Length PL2	800
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	20
Packaging Quantity PL4	120
Packaging Type PL1	Piece
Packaging Type PL2	Medium_Box

Packaging Type PL4	Pallet
Packaging Volume PL1	0,00839644
Packaging Volume PL2	0,192
Packaging Volume PL4	1,44
Packaging Weight PL1	0,811
Packaging Weight PL2	16,22
Packaging Weight PL4	122,32
Packaging Width PL1	268
Packaging Width PL2	600
Packaging Width PL4	1000

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb