


GF HT-PP pipe with single socket 32x2000mm

1150822

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with single socket

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with single socket 32x2000mm

1150822



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652042343
Item no GF	4801003200621
Item no GTIN	08698652042343
Item no VVS	186020200

Dimensions

Item Unit Height	32
Item Unit Length	2000
Item Unit Weight	0,41
Item Unit Width	32
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900551816
Packaging GTIN PL2	06414900233354
Packaging Height PL1	32
Packaging Height PL2	175
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,002048
Packaging Volume PL2	0,0245
Packaging Weight PL1	0,41
Packaging Weight PL2	4,1

Packaging Width PL1	32
Packaging Width PL2	70
Measurements	
Wall thickness_s	20
Z Measurement d	39
Z Measurement d1	32
Z Measurement e	1,8
Z Measurement L1	45

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com