

GF HT-PP pipe with double socket S20 50x2000mm

1150830

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with double socket S20

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with double socket S20 50x2000mm

1150830



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652039169
Item no GF	4801005020221
Item no GTIN	08698652039169
Item no VVS	186072200

Dimensions

Item Unit Height	50
Item Unit Length	2000
Item Unit Weight	0,668
Item Unit Width	50
Item_UOM	pce

Measurements

Length (l2)	50
Z Measurement b1	5
Z Measurement b2	5
Z Measurement d	60
Z Measurement d1	50,5
Z Measurement d3	50,5
Z Measurement d3	50,5
Z Measurement d4	60
Z Measurement e	1,8
Z measurement m	46

Packaging

Packaging GTIN PL1	06414900552059
Packaging GTIN PL2	06414900233439
Packaging Height PL1	50

Packaging Height PL2	275
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,005
Packaging Volume PL2	0,066
Packaging Weight PL1	0,668
Packaging Weight PL2	6,68
Packaging Width PL1	50
Packaging Width PL2	120

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com