

GF HT-PP pipe with double socket S20 50x1000mm

1150832

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with double socket S20

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with double socket S20 50x1000mm

1150832



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652092010
Item no GF	4801005020421
Item no GTIN	08698652092010
Item no VVS	186072100

Dimensions

Item Unit Height	50
Item Unit Length	1000
Item Unit Weight	0,373
Item Unit Width	50
Item_UOM	pce

Measurements

Length (l2)	50
Z Measurement b1	5
Z Measurement b2	5
Z Measurement d	60
Z Measurement d1	50,5
Z Measurement d3	50,5
Z Measurement d3	50,5
Z Measurement d4	60
Z Measurement e	1,8
Z measurement m	46

Packaging

Packaging GTIN PL1	06414900552035
Packaging GTIN PL2	06414900233453
Packaging Height PL1	50

Packaging Height PL2	275
Packaging Length PL1	1000
Packaging Length PL2	1000
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,0025
Packaging Volume PL2	0,033
Packaging Weight PL1	0,373
Packaging Weight PL2	3,73
Packaging Width PL1	50
Packaging Width PL2	120

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
 WD18 8GA, Watford
 UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfischer.com