

GF HT-PP pipe with double socket S20 75x3000mm

1150838

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with double socket S20

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with double socket S20 75x3000mm

1150838



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652091990
Item no GF	4801007520621
Item no GTIN	08698652091990
Item no VVS	186074300

Dimensions

Item Unit Height	75
Item Unit Length	3000
Item Unit Weight	1,587
Item Unit Width	75
Item_UOM	pce

Measurements

Length (l2)	55
Z Measurement b1	5
Z Measurement b2	5
Z Measurement d	85,2
Z Measurement d1	75,6
Z Measurement d3	75,6
Z Measurement d3	75,6
Z Measurement d4	85,2
Z Measurement e	1,9
Z measurement m	51

Packaging

Packaging GTIN PL1	06414900552097
Packaging GTIN PL2	06414900233507
Packaging Height PL1	75

Packaging Height PL2	400
Packaging Length PL1	3000
Packaging Length PL2	3000
Packaging Quantity PL1	1
Packaging Quantity PL2	10
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,016875
Packaging Volume PL2	0,204
Packaging Weight PL1	1,587
Packaging Weight PL2	15,87
Packaging Width PL1	75
Packaging Width PL2	170

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfi
scher.com