

GF HT-PP pipe with double socket S20 110x2000mm

1150846

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with double socket S20

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with double socket S20 110x2000mm

1150846



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652039282
Item no GF	4801011020821
Item no GTIN	08698652039282
Item no VVS	186077200

Dimensions

Item Unit Height	110
Item Unit Length	2000
Item Unit Weight	2,23
Item Unit Width	110
Item_UOM	pce

Measurements

Length (l2)	65
Z Measurement b1	6
Z Measurement b2	6
Z Measurement d	120,6
Z Measurement d1	110,5
Z Measurement d3	110,5
Z Measurement d3	110,5
Z Measurement d4	120,6
Z Measurement e	2,7
Z measurement m	58

Packaging

Packaging GTIN PL1	06414900600316
Packaging GTIN PL2	06414900233569
Packaging Height PL1	110

Packaging Height PL2	250
Packaging Length PL1	2000
Packaging Length PL2	2000
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,0242
Packaging Volume PL2	0,125
Packaging Weight PL1	2,23
Packaging Weight PL2	8,92
Packaging Width PL1	110
Packaging Width PL2	250

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
 WD18 8GA, Watford
 UK

T +44 (0)1923 381212

E
customerservice.uk.bfs@georgfischer.com