

## GF HT-PP pipe with double socket S20 110x3000mm

**1150847**

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



### About GF HT-PP pipe with double socket S20

#### Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

#### Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

## GF HT-PP pipe with double socket S20 110x3000mm

1150847



### Status

Item Available From date 2026-03-01

### Product code

Item no EAN	8698652039299
Item no GF	4801011020921
Item no GTIN	08698652039299
Item no VVS	186077300

### Dimensions

Item Unit Height	110
Item Unit Length	3000
Item Unit Weight	3,288
Item Unit Width	110
Item_UOM	pce

### Measurements

Length (l2)	65
Z Measurement b1	6
Z Measurement b2	6
Z Measurement d	120,6
Z Measurement d1	110,5
Z Measurement d3	110,5
Z Measurement d3	110,5
Z Measurement d4	120,6
Z Measurement e	2,7
Z measurement m	58

### Packaging

Packaging GTIN PL1	06414900600347
Packaging GTIN PL2	06414900233576
Packaging Height PL1	110

Packaging Height PL2	250
Packaging Length PL1	3000
Packaging Length PL2	3000
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,0363
Packaging Volume PL2	0,1875
Packaging Weight PL1	3,288
Packaging Weight PL2	13,152
Packaging Width PL1	110
Packaging Width PL2	250

## Technical documents

[Download documents here](#)

### Uponor UK

Blackmor Lane The Pavillion  
WD18 8GA, Watford  
UK

T +44 (0)1923 381212  
E  
customerservice.uk.bfs@georgfi  
scher.com