

GF HT-PP pipe with double socket S20 125x3000mm

1150854

- Where detailed Class is S20 to BS EN 1451
- Grey, monolayer, PP-material
- According to BS EN 1451



About GF HT-PP pipe with double socket S20

Specification

- Manufactured using chemical and temperature resistant Polypropylene
- System according to the requirements of BS EN 1451
- Application area B to BS EN 1451
- Fire class E to BS EN 13501-1
- Pipe diameters from 32 mm to 160 mm
- Wide range of fittings to give complete design freedom
- For use with GF standard Clamp fittings

Application

- Office buildings and conference halls
- Schools, libraries, hospitals, hotels, and residential buildings
- Sustainable and green buildings
- Industrial facilities for both short- and long-term applications
- Ideal for pre-fabricated buildings

GF HT-PP pipe with double socket S20 125x3000mm

1150854



Status

Item Available From date 2026-03-01

Product code

Item no EAN	8698652039350
Item no GF	4801012521321
Item no GTIN	08698652039350
Item no VVS	186078300

Dimensions

Item Unit Height	125
Item Unit Length	3000
Item Unit Weight	4,307
Item Unit Width	125
Item_UOM	pce

Measurements

Length (l2)	65
Z Measurement b1	7
Z Measurement b2	7
Z Measurement d	136,9
Z Measurement d1	125,5
Z Measurement d3	125,5
Z Measurement d3	125,5
Z Measurement d4	136,9
Z Measurement e	3,1
Z measurement m	64

Packaging

Packaging GTIN PL1	06414900600354
Packaging GTIN PL2	06414900233590
Packaging Height PL1	125

Packaging Height PL2	275
Packaging Length PL1	3000
Packaging Length PL2	3000
Packaging Quantity PL1	1
Packaging Quantity PL2	4
Packaging Type PL1	Piece
Packaging Type PL2	Bag
Packaging Volume PL1	0,046875
Packaging Volume PL2	0,226875
Packaging Weight PL1	4,307
Packaging Weight PL2	17,228
Packaging Width PL1	125
Packaging Width PL2	275

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com