



GF iFIT adapter 16

1151108

- Material: PPSU, PA
- PN 16 at 20°C



About GF iFIT adapter

Specification

- The iFIT system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety. The iFIT system meets the requirements for the most important applications in the building technology and is subject to constant monitoring
- by the licensing offices for drinking water and heating installations on land and sea.

Application


- Application area Cold and hot water, HVAC, greywater
-
- Installation Surface and flush-mounted pipes, pipe-in-pipe technology

Certification

- SVGW
- DVGW
- ÖVGW

GF iFIT adapter 16

1151108



Measurements

Inner_diameter_di	30
LENGTH_L	48
Z	5

Product code

Item no EAN	7611205884918
Item no GF	762101030
Item no GTIN	07611205884918
Item no LVI	1749396
Item no RSK	1878640

Dimensions

Item Unit Height	30
Item Unit Length	49
Item Unit Weight	0,024
Item Unit Width	27
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205906092
Packaging GTIN PL2	07611205906085
Packaging GTIN PL4	06414900118781
Packaging Height PL1	40
Packaging Height PL2	225
Packaging Height PL4	1150
Packaging Length PL1	230
Packaging Length PL2	410
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	150

Packaging Quantity PL4	6750
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00184
Packaging Volume PL2	0,02444625
Packaging Volume PL4	1,104
Packaging Weight PL1	0,243
Packaging Weight PL2	3,918
Packaging Weight PL4	200
Packaging Width PL1	200
Packaging Width PL2	265
Packaging Width PL4	800

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb