



GF iFIT adapter 20

1151109

- Material: PPSU, PA
- PN 16 at 20°C



About GF iFIT adapter

Specification

- The iFIT system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety. The iFIT system meets the requirements for the most important applications in the building technology and is subject to constant monitoring by the licensing offices for drinking water and heating installations on land and sea.

Application


- Application area Cold and hot water, HVAC, greywater
-
- Installation Surface and flush-mounted pipes, pipe-in-pipe technology

Certification

- SVGW
- DVGW
- ÖVGW

GF iFIT adapter 20

1151109



Measurements

Inner_diameter_di	34
LENGTH_L	49
Z	5

Product code

Item no EAN	7611205884925
Item no GF	762101031
Item no GTIN	07611205884925
Item no LVI	1749397
Item no RSK	1878641

Dimensions

Item Unit Height	32
Item Unit Length	51
Item Unit Weight	0,028
Item Unit Width	32
Item_UOM	pce

Packaging

Packaging GTIN PL1	07611205904876
Packaging GTIN PL2	07611205904869
Packaging GTIN PL4	06414900118774
Packaging Height PL1	63
Packaging Height PL2	225
Packaging Height PL4	1200
Packaging Length PL1	155
Packaging Length PL2	410
Packaging Length PL4	1200
Packaging Quantity PL1	10
Packaging Quantity PL2	150

Packaging Quantity PL4	6750
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,001474515
Packaging Volume PL2	0,02444625
Packaging Volume PL4	1,152
Packaging Weight PL1	0,302
Packaging Weight PL2	4,816
Packaging Weight PL4	237
Packaging Width PL1	151
Packaging Width PL2	265
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
 WD18 8GA, Watford
 UK

T +44 (0)1923 927000
 E enquiries.uk@uponor.com

www.uponor.com/en-gb