



GF iFIT manifold shut-off valve LF 25/32-3/4"

1151310

- Temperature: max. 90°C
- Material: gunmetal lead-free
- Connection: female thread, iFIT



About GF iFIT manifold shut-off valve LF

Specification

- The iFIT system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety. The iFIT system meets the requirements for the most important applications in the building technology and is subject to constant monitoring by the licensing offices for drinking water and heating installations on land and sea.

Application



- Application area Cold and hot water, HVAC, greywater
-
- Installation Surface and flush-mounted pipes, pipe-in-pipe technology

Certification

- SVGW
- DVGW
- ÖVGW

GF iFIT manifold shut-off valve LF 25/32-3/4"

1151310



Measurements

Cylindric thread G3	3/4
Female thread Rp2	3/4
Length (l2)	52
Z Measurement d	25 - 32
Z Measurement d2	3/4
Z Measurement d3	3/4
Z Measurement d3	3/4
Z Measurement d4	53
Z Measurement h	82
z1	23

Product code

Item no EAN	7613263115690
Item no GF	762102229
Item no GTIN	07613263115690

Dimensions

Item Unit Height	97
Item Unit Length	93
Item Unit Weight	0,44
Item Unit Width	51
Item_UOM	pce

Packaging

Packaging GTIN PL2	06414900133784
Packaging Height PL2	61
Packaging Length PL2	122
Packaging Quantity PL2	1
Packaging Type PL2	Medium_Box
Packaging Volume PL2	0,001220488

Packaging Weight PL2	0,61
Packaging Width PL2	164

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavillion
WD18 8GA, Watford
UK

T +44 (0)1923 381212
E
customerservice.uk.bfs@georgfi
scher.com