


GF iFIT male thread adapter LF 25/32-1"

1151316

- Material: gunmetal lead-free
- Connection: male thread
- PN 16 at 20°C



About GF iFIT male thread adapter LF

Specification

- The iFIT system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety. The iFIT system meets the requirements for the most important applications in the building technology and is subject to constant monitoring by the licensing offices for drinking water and heating installations on land and sea.

Application


- Application area Cold and hot water, HVAC, greywater
-
- Installation Surface and flush-mounted pipes, pipe-in-pipe technology

Certification

- SVGW
- DVGW
- ÖVGW

GF iFIT male thread adapter LF 25/32-1"

1151316



Product code

Item no EAN	7611205913229
Item no GF	762102278
Item no GTIN	07611205913229
Item no LVI	1749420

Dimensions

Item Unit Height	41
Item Unit Length	54.4
Item Unit Weight	0,185
Item Unit Width	41
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900080606
Packaging GTIN PL2	06414900080613
Packaging GTIN PL4	06414900080620
Packaging Height PL1	45
Packaging Height PL2	150
Packaging Height PL4	1000
Packaging Length PL1	78
Packaging Length PL2	265
Packaging Length PL4	1200
Packaging Quantity PL1	2
Packaging Quantity PL2	20
Packaging Quantity PL4	1600
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,00026676

Packaging Volume PL2	0,00616125
Packaging Volume PL4	0,96
Packaging Weight PL1	0,38
Packaging Weight PL2	3,9
Packaging Weight PL4	337
Packaging Width PL1	76
Packaging Width PL2	155
Packaging Width PL4	800
Measurements	
Z Measurement h	57

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb