


GF Instaflex tee reduced 90deg 25-16 25

1152202

- Made of Polybuten



About GF Instaflex tee reduced 90deg

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas

- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex tee reduced 90deg 25-16 25

1152202



Measurements

Inner_diameter_di	25
Length (l2)	32
Length (l3)	32
Z Measurement d2	16
z1	14
Z2	17
Z3	14

Product code

Item no EAN	7611205819682
Item no GF	761066917
Item no GTIN	07611205819682
Item no RSK	1874834

Dimensions

Item Unit Height	40
Item Unit Length	60
Item Unit Weight	0,025
Item Unit Width	60
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900065375
Packaging Height PL1	42
Packaging Length PL1	70
Packaging Quantity PL1	10
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000882
Packaging Weight PL1	0,26
Packaging Width PL1	300

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb