



GF Instaflex tee reduced 90deg 40-32 40

1152268

- Made of Polybuten



About GF Instaflex tee reduced 90deg

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas

- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex tee reduced 90deg 40-32 40

1152268



Measurements

Inner_diameter_di	40
Length (l2)	44
Length (l3)	44
Z Measurement d2	32
z1	22
Z2	24
Z3	22

Product code

Item no EAN	7611205900908
Item no GF	761068049
Item no GTIN	07611205900908

Dimensions

Item Unit Height	70
Item Unit Length	88
Item Unit Weight	0,076
Item Unit Width	51
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900455206
Packaging GTIN PL2	06414900455213
Packaging Height PL1	40
Packaging Height PL2	420
Packaging Length PL1	350
Packaging Length PL2	790
Packaging Quantity PL1	5
Packaging Quantity PL2	250
Packaging Type PL1	Plastic_Bag

Packaging Type PL2	Medium_Box
Packaging Volume PL1	0,0028
Packaging Volume PL2	0,195762
Packaging Weight PL1	0,43
Packaging Weight PL2	21,7
Packaging Width PL1	200
Packaging Width PL2	590

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb