



GF Instaflex tee reduced 90deg 50-32 50

1152269

- Made of Polybuten



About GF Instaflex tee reduced 90deg

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas

- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex tee reduced 90deg 50-32 50

1152269



Measurements

Inner_diameter_di	50
Length (l2)	51
Length (l3)	51
Z Measurement d2	32
z1	26
Z2	31
Z3	26

Product code

Item no EAN	7611205900915
Item no GF	761068050
Item no GTIN	07611205900915

Dimensions

Item Unit Height	76
Item Unit Length	103
Item Unit Weight	0,133
Item Unit Width	64
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900455220
Packaging GTIN PL2	06414900455237
Packaging Height PL1	200
Packaging Length PL1	110
Packaging Quantity PL1	5
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,00143
Packaging Weight PL1	0,675
Packaging Width PL1	65

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb