



GF Instaflex tee reduced 90deg 63-32 63

1152270

- Made of Polybuten



About GF Instaflex tee reduced 90deg

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas

- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex tee reduced 90deg 63-32 63

1152270



Measurements

Inner_diameter_di	63
Length (l2)	62
Length (l3)	62
Z Measurement d2	32
z1	34
Z2	42
Z3	34

Product code

Item no EAN	7611205900922
Item no GF	761068051
Item no GTIN	07611205900922

Dimensions

Item Unit Height	100
Item Unit Length	150
Item Unit Weight	0,255
Item Unit Width	100
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900112130
Packaging Height PL1	300
Packaging Length PL1	150
Packaging Quantity PL1	5
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,009
Packaging Weight PL1	1,3
Packaging Width PL1	200

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb