


GF Instaflex weld machine Electro Fusion G3 L300

1152285

- Including welding cable for fittings without tool case, primary cable 110V, primary cable 230V
- Primary cable (3m) with Euro standard plug EU-Standard plug
- Technical data: voltage 110V and 230V variable, power output max. 1500W
- Technical specifications: frequency 47/65Hz, protection rate IP54, incl. power-supply cable 110V and 230V (3m)
- With EU-Standard plug
- * on request



About GF Instaflex weld machine Electro Fusion G3

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas


- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex weld machine Electro Fusion G3 L300

1152285



Product code

Item no EAN	7611205812416
Item no GF	761069015
Item no GTIN	07611205812416

Dimensions

Item Unit Height	330
Item Unit Length	300
Item Unit Weight	11,5
Item Unit Width	150
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900112208
Packaging Height PL1	250
Packaging Length PL1	600
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,075
Packaging Weight PL1	11,6015239453618
Packaging Width PL1	500

Technical documents

Download documents here

uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb