

GF Instaflex tee equal 90deg Electro Fusion d32

1152326

- PN 16 at 20°C



About GF Instaflex tee equal 90deg Electro Fusion

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas

- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex tee equal 90deg Electro Fusion d32

1152326



Product code

Item no EAN	7611205820534
Item no GF	761069240
Item no GTIN	07611205820534
Item no LVI	2075384
Item no RSK	1874673

Dimensions

Item Unit Height	54
Item Unit Length	121
Item Unit Weight	0,116
Item Unit Width	87
Item_UOM	pce

Measurements

LENGTH_L	60
Z	18

Packaging

Packaging GTIN PL1	06414900189323
Packaging GTIN PL2	06414900189330
Packaging GTIN PL4	06414900189347
Packaging Height PL1	54
Packaging Height PL2	305
Packaging Height PL4	950
Packaging Length PL1	121
Packaging Length PL2	406
Packaging Length PL4	1200
Packaging Quantity PL1	1
Packaging Quantity PL2	25
Packaging Quantity PL4	900

Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Type PL4	Pallet
Packaging Volume PL1	0,000568458
Packaging Volume PL2	0,03974943
Packaging Volume PL4	0,912
Packaging Weight PL1	0,124
Packaging Weight PL2	3,1
Packaging Weight PL4	125
Packaging Width PL1	87
Packaging Width PL2	321
Packaging Width PL4	800

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb