

## GF Instaflex reducer electro fusion d25-20

1152361

- Material: Polybutene (grey)



### About GF Instaflex reducer electro fusion

#### Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

#### Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

##### Application areas

- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

#### Certification

- WRAS material approval (BS6920)

## GF Instaflex reducer electro fusion d25-20

1152361



### Measurements

Inner_diameter_di	25
LENGTH_L	42
Z Measurement d1	25
Z Measurement d2	20
Z Measurement h	86
Z	47

### Product code

Item no EAN	7611205823818
Item no GF	761069279
Item no GTIN	07611205823818
Item no LVI	2075394
Item no RSK	1874554

### Dimensions

Item Unit Height	41
Item Unit Length	88
Item Unit Weight	0,026
Item Unit Width	41
Item_UOM	pce

### Packaging

Packaging GTIN PL1	06414900455367
Packaging GTIN PL2	06414900455374
Packaging Height PL1	41
Packaging Height PL2	280
Packaging Length PL1	88
Packaging Length PL2	400
Packaging Quantity PL1	1
Packaging Quantity PL2	100

Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box
Packaging Volume PL1	0,000147928
Packaging Volume PL2	0,03024
Packaging Weight PL1	0,03
Packaging Weight PL2	3,353
Packaging Width PL1	41
Packaging Width PL2	270

## Technical documents

Download documents here 

### Uponor UK

Blackmor Lane The Pavillion  
WD18 8GA, Watford  
UK

T +44 (0)1923 381212  
E  
customerservice.uk.bfs@georgfi  
scher.com