

GF Instaflex reducer electro fusion Electro Fusion d25-20

1152361

- Material: Polybutene (grey)



About GF Instaflex reducer electro fusion Electro Fusion

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification
- for environmental and process safety. The INSTAFLEX system meets all the essential
- requirements for building technology applications and is subject to constant monitoring by the
- licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas

- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex reducer electro fusion Electro Fusion d25-20

1152361



Measurements

Inner_diameter_di	25
Z Measurement d2	20
Z Measurement h	86
Z	47

Product code

Item no EAN	7611205823818
Item no GF	761069279
Item no GTIN	07611205823818
Item no LVI	2075394
Item no RSK	1874554

Dimensions

Item Unit Height	41
Item Unit Length	88
Item Unit Weight	0,026
Item Unit Width	41
Item_UOM	pce

Packaging

Packaging GTIN PL1	06414900455367
Packaging GTIN PL2	06414900455374
Packaging Height PL1	41
Packaging Height PL2	280
Packaging Length PL1	88
Packaging Length PL2	400
Packaging Quantity PL1	1
Packaging Quantity PL2	100
Packaging Type PL1	Plastic_Bag
Packaging Type PL2	Medium_Box

Packaging Volume PL1	0,000147928
Packaging Volume PL2	0,03024
Packaging Weight PL1	0,03
Packaging Weight PL2	3,353
Packaging Width PL1	41
Packaging Width PL2	270

Technical documents

Download documents here 

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb