


GF Instaflex straight thread MT 20-1/2"

1152564

- Socket fusion transition to male thread
- Thread in DZR brass, UBA listed
- Gasket: EPDM
- Material: PB, Brass
- Operating pressure: 16 bars



About GF Instaflex straight thread MT

Specification

- The system is subject to constant inspection by internal and external bodies.
- These inspections range from quality assurance during production to ISO certification for environmental and process safety. The INSTAFLEX system meets all the essential requirements for building technology applications and is subject to constant monitoring by the licensing offices for drinking water, heating and compressed air installations on land and sea.

Application

Instaflex offers complete solutions for single-family homes, multi-family residential buildings, healthcare, education, industrial, or commercial building

Application areas

- hot & cold water, compressed air, cooling systems
- Surface and flush-mounted pipelines

Certification

- WRAS material approval (BS6920)

GF Instaflex straight thread MT 20-1/2"

1152564



Product code

Item no EAN	7611205903367
Item no GF	761069667
Item no GTIN	07611205903367

Dimensions

Item Unit Height	101.2
Item Unit Length	31.2
Item Unit Weight	0,106
Item Unit Width	31.2
Item_UOM	pce

Measurements

LENGTH_L	99
Z	86

Packaging

Packaging GTIN PL1	06414900113281
Packaging Height PL1	101.2
Packaging Length PL1	31.2
Packaging Quantity PL1	1
Packaging Type PL1	Plastic_Bag
Packaging Volume PL1	0,000098512128
Packaging Weight PL1	0,156
Packaging Width PL1	31.2

Technical documents

[Download documents here](#)

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb